

Plant Room Floor Painting

High build flexible polyurethane floor paint

Industrial Floor Treatments (Stone) Ltd

PO Box 3701, Stone, Staffordshire, ST15 9ES

Tel: 01785 819800

BS 8204-6 FeRFA Type 3 High Build Floor Coating

enquiries@iftstone.co.uk

www.iftstone.co.uk



Plant Room Floor - Type 3 High Build Flexible Polyurethane Resin Floor Paint

Two coats of high build is equivalent in thickness of up to 10 coats of single pack industrial and garage floor paint

Description

A thick two-pack flexible polyurethane resin floor paint with crack-bridging properties. A hard wearing polyurethane resin floor paint offering excellent abrasion and chemical resistance. Anti-slip finishes available.

Suitable Surfaces

Asphalt, timber, steel, concrete and polymer screeds

Appearance

Medium gloss finish available in a range of colours. A selection of RAL or BS 4800 colours are available upon request.

Benefits

- Protects from oil and chemical spillages
- Flexible with crack bridging capability
- High build with excellent wear resistance
- Gloss, easy to clean finish
- Light reflective & non dusting

Thickness

0.4mm from two coats - this is equivalent in thickness of up to 10 coats of single pack industrial and garage floor paints.

Typical Uses

Hard wearing coloured polyurethane resin floor paint for plant rooms, warehouses, engineering plants, factories, assembly and production areas, vehicle workshops, aircraft hangars and storage areas. Excellent chemical resistance

Traffic

Suitable for regular foot traffic, frequent forklift truck traffic and occasional hard plastic-wheeled trolleys.

Application Conditions

The ambient temperature should be 10oC or higher and the concrete floor slab temperature not less than 5oC.

Existing Floors

The building must be wind and watertight and all surfaces in a clean, sound and dry condition.



Light Grey



Mid Grey



Dark Grey



Red



Green



Light Blue



Mid Blue



Chelsea Blue



Buff



Safety Yellow